

What is claimed is:

1. A method for correcting an image frame, the method comprising:

receiving a first image frame from a digital sensor;

receiving a plurality of image frames from the digital sensor exposed to light  
5 below a first predefined luminance level;

receiving a plurality of image frames from the digital sensor exposed to light  
above a second predefined luminance level; and

correcting the first received image frame based on the received plurality of image  
frames exposed to light below the first predefined luminance level and the  
10 plurality of image frames exposed to light above the second predefined  
luminance level.

2. The method of Claim 1, wherein each image frame includes a plurality of frame  
units and correcting includes:

calculating a mean value for each frame unit of the plurality of image frames  
15 exposed to light below the first predefined luminance level;

calculating a mean value for each frame unit of the plurality of image frames  
exposed to light above the second predefined luminance level;

generating a second image frame by subtracting the calculated mean value for  
each frame unit of the plurality of image frames exposed to light below the  
20 first predefined luminance level from the corresponding frame unit in the first  
image frame;

generating a third image frame by subtracting the calculated mean value for each  
frame unit of the plurality of image frames exposed to light below the first  
predefined luminance level from the calculated mean value for each  
25 corresponding frame unit of the plurality of image frames exposed to light  
above the second predefined luminance level;

generating a fourth image frame by dividing each frame unit in the second image  
frame from the corresponding frame unit in the third image frame;

calculating an average of frame units within a predefined center section of the  
30 third image frame; and

generating a fifth image frame by multiplying each frame unit in the fourth image  
frame by the calculated average of the center section frame units, thereby  
producing a corrected image frame of the received image frame.



3. The method of Claim 2, wherein generating a fifth image frame includes adding a first predefined constant value.

4. The method of Claim 3, wherein the first constant value is around 150 based on sensor testing and characterizations.

5. The method of Claim 1, wherein receiving the image frames includes enhancing the image frames based on characteristics of the digital sensor.

6. The method of Claim 5, wherein enhancing the image frames includes:  
determining a region of interest based on a masked region of the digital sensor;  
determining a standard deviation of the frame units for the determined region of interest;  
determining a threshold value based on the determined standard deviation;  
determining a mean of the frame units in the determined region of interest that are below the determined threshold value; and  
generating enhanced image frames based on the determined mean of the frame units.

7. The method of Claim 6, wherein generating enhanced image frames includes:  
determining a mean difference value based on the determined mean of the frame units and a predefined coefficient; and  
adding the determined mean difference value to each frame unit of the corresponding image frame.

8. The method of Claim 7, wherein determining a mean difference value includes subtracting the determined mean of the frame units from 150.

9. The method of Claim 6, wherein determining a threshold value includes multiplying the determined standard deviation by a second constant value.

10. The method of Claim 9, wherein the second constant value is around 6.

11. The method of Claim 5, wherein receiving the first image frame includes removing light scattering effects from a portion of the enhanced image frame based upon light scattering properties.



12. The method of Claim 11, wherein the light scattering properties include light scattering effects of the frame units upon all other frame units based upon distance between the respective frame units.

13. The method of Claim 12, wherein removing light scattering effects includes:

- a) calculating an average value of frame units within the determined region of interest;
- b) generating a second image frame and by removing the calculated average value from each of the frame units of the enhanced first image frame;
- c) separating the second image frame into a plurality of subarrays;
- d) generating a total for each subarray by adding all the frame units of the respective subarray;
- e) determining a distance of a frame unit of the second image frame from one of the subarrays;
- f) determining the light scattering effect of the subarray upon the frame unit based upon the determined distance of the frame unit from the subarray and predetermined light scattering characteristics;
- g) generating a subarray light scattering effect by multiplying the determined light scattering effect by the generated total of the associated subarray;
- h) repeating e) - g) for all the subarrays;
- i) generating a subarray effects total by adding all the generated subarray light scattering effects;
- j) generating a final frame unit by subtracting the generated subarray effects total from the respective frame unit; and
- k) repeating e) - j) for all the frame units of the second image frame.

14. A system for correcting an image frame produced by a digital sensor, the system comprising:

a processor including:

- a first component configured to receive a first image frame from the digital sensor, a plurality of image frames exposed to light below a first predefined luminance level, and a plurality of image frames exposed to light above a second predefined luminance level; and
- a second component configured to correct the first image frame based on the received plurality of image frames exposed to light below the first



25315

PATENT TRADEMARK OFFICE

predefined luminance level and the plurality of image frames exposed to light above the second predefined luminance level; and an output device configured to output the corrected image frame.

15. The system of Claim 14, wherein each image frame includes a frame unit and wherein the second component includes:

a third component configured to calculate a mean value for each frame unit of the plurality of image frames exposed to light below the first predefined luminance level;

a fourth component configured to calculate a mean value for each frame unit of the plurality of image frames exposed to light above the second predefined luminance level;

a fifth component configured to generate a second image frame by subtracting the calculated mean value for each frame unit of the plurality of image frames exposed to dark from the corresponding frame unit in the first image frame;

a sixth component configured to generate a third image frame by subtracting the calculated mean value for each frame unit of the plurality of image frames exposed to light below the first predefined luminance level from the calculated mean value for each corresponding frame unit of the plurality of image frames exposed to light above the second predefined luminance level;

a seventh component configured to generate a fourth image frame by dividing each frame unit in the second image frame from the corresponding frame unit in the third image frame;

an eighth component configured to calculate an average of frame units within a predefined center section of the third image frame; and

a ninth component configured to generate a fifth image frame by multiplying each frame unit in the fourth image frame by the calculated average of the center section frame units, thereby producing a corrected image frame of the received image frame.

16. The system of Claim 15, wherein the ninth component includes a tenth component configured to add a first predefined constant value.

17. The system of Claim 16, wherein the first constant value is around 150 based on sensor testing and characterizations.



25315

PATENT TRADEMARK OFFICE

18. The system of Claim 14, wherein the first component is configured to enhance the image frames based on characteristics of the digital sensor.

19. The system of Claim 18, wherein the first component is configured to enhance the image frames by:

5           determining a region of interest based on a masked region of the digital sensor;  
          determining a standard deviation of the frame units for the determined region of  
          interest;  
          determining a threshold value based on the determined standard deviation;  
          determining a mean of the frame units in the determined region of interest that are  
10           below the determined threshold value; and  
          generating enhanced image frames based on the determined mean of the frame  
          units.

20. The system of Claim 19, wherein the first component is configured to generate the enhanced image frames by:

15           determining a mean difference value based on the determined mean of the frame  
          units and a predefined coefficient; and  
          adding the determined mean difference value to each frame unit of the  
          corresponding image frame.

21. The system of Claim 20, wherein the predefined coefficient is about 150 based on  
20   sensor testing and characterizations.

22. The system of Claim 19, wherein the first component is configured to determine a threshold value by multiplying the determined standard deviation by a second constant value.

23. The system of Claim 22, wherein the second constant value is around 6.

24. The system of Claim 18, wherein the first component is configured to remove light  
25   scattering effects from the enhanced image frame based upon light scattering properties.

25. The system of Claim 24, wherein the light scattering properties include light scattering effects of the frame units upon all other frame units based upon the distance between the respective frame units.

26. The system of Claim 25, wherein the third component is configured to remove light  
30   scattering effects by:



- 5
- 10
- 15
- 20
- a) calculating an average value of frame units within the determined region of interest;
  - b) generating a second image frame by removing the calculated average value from each of the frame units of the enhanced first image frame;
  - c) separating the second image frame into a plurality of subarrays;
  - d) generating a total for each subarray by adding frame units of the respective subarray;
  - e) determining a distance of a frame unit of the second image frame from one of the subarrays;
  - f) determining the light scattering effect of the subarray upon the frame unit based upon the determined distance of the frame unit from the subarray and predetermined light scattering characteristics;
  - g) generating a subarray light scattering effect by multiplying the determined light scattering effect by the generated total of the associated subarray;
  - h) repeating e) - g) for all the subarrays;
  - i) generating a subarray effects total by adding all the generated subarray light scattering effects;
  - j) generating a final frame unit by subtracting the generated subarray effects total from the respective frame unit; and
  - k) repeating e) - j) for all the frame units of the second image frame.

27. A computer-program product residing on a computer readable medium for correcting an image frame produced by a digital sensor, the computer-program product comprising:

- 25
- 30
- a first computer program code component configured to receive a first image frame from the digital sensor, a plurality of image frames exposed to light below a first predefined luminance level, and a plurality of image frames exposed to light above a second predefined luminance level; and
  - a second computer program code component configured to correct the first image frame based on the received plurality of image frames exposed to light below the first predefined luminance level and the plurality of image frames exposed to light above the second predefined luminance level; and
  - a third computer program code component configured to output the corrected image frame on an output device.



25315

PATENT TRADEMARK OFFICE

28. The computer-program product of Claim 27, wherein each image frame includes a frame unit and wherein the second computer program code component includes:

a fourth computer program code component configured to calculate a mean value for each frame unit of the plurality of image frames exposed to light below the first predefined luminance level;

a fifth computer program code component configured to calculate a mean value for each frame unit of the plurality of image frames exposed to light above the second predefined luminance level;

a sixth computer program code component configured to generate a second image frame by subtracting the calculated mean value for each frame unit of the plurality of image frames exposed to light below the first predefined luminance level from the corresponding frame unit in the first image frame;

a seventh computer program code component configured to generate a third image frame by subtracting the calculated mean value for each frame unit of the plurality of image frames exposed to light below the first predefined luminance level from the calculated mean value for each corresponding frame unit of the plurality of image frames exposed to light the second predefined luminance level;

an eighth computer program code component configured to generate a fourth image frame by dividing each frame unit in the second image frame from the corresponding frame unit in the third image frame;

a ninth computer program code component configured to calculate an average of frame units within a predefined center section of the third image frame; and

a tenth computer program code component configured to generate a fifth image frame by multiplying each frame unit in the fourth image frame by the calculated average of the center section frame units, thereby producing a corrected image frame of the received image frame.

29. The computer-program product of Claim 28, wherein the tenth computer program code component includes an eleventh computer program code component configured to add a first predefined constant value.

30. The computer-program product of Claim 29, wherein the first constant value is around 150 based on sensor testing and characterizations.



25315

PATENT TRADEMARK OFFICE



31. The computer-program product of Claim 27, wherein the first computer program code component is configured to enhance the image frames based on characteristics of the digital sensor.

32. The computer-program product of Claim 31, wherein the first computer program code component is configured to enhance the image frames by:

determining a region of interest based on a masked region of the digital sensor;  
determining a standard deviation of the frame units for the determined region of interest;  
determining a threshold value based on the determined standard deviation;  
determining a mean of the frame units in the determined region of interest that are below the determined threshold value; and  
generating enhanced image frames based on the determined mean of the frame units.

33. The computer-program product of Claim 32, wherein the first computer program code component is configured to generate the enhanced image frames by:

determining a mean difference value based on determined mean of the frame units and a predefined coefficient; and  
adding the determined mean difference value to each frame unit of the corresponding image frame.

34. The computer-program product of Claim 33, wherein the predefined coefficient is about 150 based on sensor testing and characterizations.

35. The computer-program product of Claim 32, wherein the first computer program code component is configured to determine a threshold value by multiplying the determined standard deviation by a second constant value.

36. The computer-program product of Claim 35, wherein the second constant value is around 6.

37. The computer-program product of Claim 27, wherein the first computer program is further configured to remove light scattering effects from the enhanced image frame based upon light scattering properties.



25315

PATENT TRADEMARK OFFICE





38. The computer-program product of Claim 37, wherein the light scattering properties include light scattering effects of the frame units upon all other frame units based upon distance between the respective frame units.

5 39. The computer-program product of Claim 38, wherein the twelfth computer program code component is configured to remove light scattering effects by:

- a) calculating an average value of frame units within the determined region of interest;
- b) generating a second image frame by removing the calculated average value from each of the frame units of the enhanced first image frame;
- 10 c) separating the second image frame into a plurality of subarrays;
- d) generating a total for each subarray by adding frame units of the respective subarray;
- e) determining a distance of a frame unit of the second image frame from one of the subarrays;
- 15 f) determining the light scattering effect of the subarray upon the frame unit based upon the determined distance of the frame unit from the subarray and predetermined light scattering characteristics;
- g) generating a subarray light scattering effect by multiplying the determined light scattering effect by the generated total of the associated subarray;
- 20 h) repeating e) - g) for all the subarrays;
- i) generating a subarray effects total by adding all the generated subarray light scattering effects;
- j) generating a final frame unit by subtracting the generated subarray effects total from the respective frame unit; and
- 25 k) repeating e) - j) for all the frame units of the second image frame.

40. A method for removing light scattering effects from an image frame generated by a digital sensor, the method comprising:

- a) receiving a first image frame from the digital sensor;
- 30 b) calculating an average value of frame units within a predetermined region of interest of the received image frame;
- c) generating a second image frame by removing the calculated average value from each of the frame units of the first image frame;
- d) separating the second image frame into a plurality of subarrays;



25315

PATENT TRADEMARK OFFICE

- e) generating a total for each subarray by adding frame units of the respective subarray;
- f) determining a distance of a subarray from a frame unit;
- g) determining light scattering effects based upon the determined distance and predetermined light scattering characteristics;
- h) generating a subarray light scattering effect by multiplying the determined light scattering effect by the generated total of the associated subarray;
- i) repeating f) - h) for processing all the subarrays;
- j) generating a subarray effects total by adding all the generated subarray light scattering effects;
- k) generating a final frame unit by subtracting the generated subarray effects total from the respective frame unit; and
- l) repeating f) - k) for processing all the frame units of the second image frame.

41. A system for removing light scattering effects from an image frame generated by a digital sensor, the system comprising:

a processor including:

- a first component configured to receive a first image frame from the digital sensor; a plurality of image frames exposed to light below a first predefined luminance level, and a plurality of image frames exposed to light above a second predefined luminance level;
- a second component configured to calculate an average value of frame units within a predetermined region of interest of the first image frame;
- a third component configured to generate a second image frame by removing the calculated average value from each of the frame units of the first image frame;
- a fourth component configured to separate the second image frame into a plurality of subarrays;
- a fifth component configured to generate a total for each subarray by adding frame units of the respective subarray;
- a sixth component configured to determine a distance of a frame unit of the second image frame from one of the subarrays;
- a seventh component configured to determine the light scattering effect of the subarray upon the frame unit based upon the determined distance



25315

PATENT TRADEMARK OFFICE

of the frame unit from the subarray and predetermined light scattering characteristics;  
an eighth component configured to generate a subarray light scattering effect by multiplying the determined light scattering effect by the generated total of the associated subarray;  
5 a ninth component configured to return to the sixth component until all the subarrays have been analyzed;  
a tenth component configured to generate a subarray effects total by adding all the generated subarray light scattering effects;  
10 an eleventh component configured to generate a final frame unit by subtracting the generated subarray effects total from the respective frame unit; and  
a twelfth component configured to return to the sixth component for processing all the frame units of the second image frame; and  
15 an output device configured to output the result of the twelfth component.

42. A computer-program product residing on a computer readable medium for removing light scattering effects from an image frame generated by a digital sensor, the computer-program product comprising:

20 a first component configured to receive a first image frame from the digital sensor; a plurality of image frames exposed to light below a first predefined luminance level, and a plurality of image frames exposed to light above a second predefined luminance level;  
a second component configured to calculate an average value of frame units within a predetermined region of interest of the first image frame;  
25 a third component configured to generate a second image frame by removing the calculated average value from each of the frame units of the first image frame;  
a fourth component configured to separate the second image frame into a plurality of subarrays;  
a fifth component configured to generate a total for each subarray by adding  
30 frame units of the respective subarray;  
a sixth component configured to determine a distance of a frame unit of the second image frame from one of the subarrays;  
a seventh component configured to determine the light scattering effect of the subarray upon the frame unit based upon the determined distance of the frame  
35 unit from the subarray and the light scattering effects;



an eighth component configured to generate a subarray light scattering effect by multiplying the determined light scattering effect by the generated total of the associated subarray;

5 a ninth component configured to return to the sixth component for all the subarrays;

a tenth component configured to generate a subarray effects total by adding all the generated subarray light scattering effects;

an eleventh component configured to generate a final frame unit by subtracting the generated subarray effects total from the respective frame unit;

10 a twelfth component configured to return to the sixth component for processing all the frame units of the second image frame; and

a thirteenth component configured to output the result of the twelfth component to an output device.

43. A method for generating an image, the method comprising:

15 collecting a digital image of a designated area of the ground from a sensor in an airborne vehicle;

correcting the collected image based on characteristics of the sensor; and  
distributing the correcting image.

20

